



PRODUCT DESCRIPTION

Designed for customers seeking a premium and efficient solution, this refrigerated air dryer helps to ensure a nominal dew point of 3°C, providing reliable moisture control across various industrial applications. Its performance helps prevent corrosion, enhance equipment longevity, and maintain air quality, making it an ideal choice for versatile, high-performance compressed air systems.

All DONALDSON BURAN compressed air refrigerated dryers enable optimum counter-flow heat exchange over the entire section. The compressed air flows over the entire section inside the heat exchanger in a top-down direction. This circulation takes place without any unfavorable deviations.

MAIN FEATURES & BENEFITS

- **The efficient drying solution**

Our BURAN refrigerated compressed air dryers are an efficient method for drying compressed air. Their basic principle is based on condensation caused by cooling; by lowering the temperature of the compressed air, the water vapor contained in it is transformed into water and is then evacuated.

- **An efficient nominal dew point at 3°C compatible with many industries**

Our BURAN dryer maintains a nominal dew point of 3°C with a range availability from 20 to 1000 m³/h, supporting efficient moisture removal suitable for a wide range of industrial applications, including pneumatics, automation, and general manufacturing. This level of dryness helps prevent corrosion, contamination, and equipment damage, making it a reliable solution for compressed air systems.

- **Easy to handle and maintain**

With a simple plug-and-play design, these dryers are easy to install and require minimal maintenance, maximizing uptime and reducing production costs. Available with timed or electronic level-controlled condensate drain including function monitoring and alarm messages for discharging of the compressed air condensate at the heat exchanger.

INDUSTRIES



- Industrial Machinery
- Food & Beverage
- Automation
- General Manufacturing


PRODUCT DESCRIPTION

The compressed air is being fed into the dryer and being pre-cooled in the air-to-air heat exchanger by the outgoing cold compressed air. The pre-cooled air then passes through the refrigerant-to-air heat exchanger where it is being further cooled down to the required pressure dew point. The moisture in the compressed air condenses out, gathers and discharges automatically. Finally, the cold discharged air is being reheated by the incoming compressed air, which helps save energy and prevents any moisture forming beyond the dryer in the compressed air system. The cooling capacity of the refrigeration cycle is being controlled by a hot gas bypass which supports the dryer functionality for partial loads.

18 sizes for nominal flow rates up to 1,000 m³/h enable accurate selection of the suitable refrigerated compressed air dryer on the respective actual flow rate.

Typical applications for the BURAN refrigerated compressed air dryers are:

- Central compressed air purification
Supports the generation of dry, oil-free and particulate-free compressed air
- Automotive industry
Supports the purification of compressed air for painting applications



PRODUCT DESCRIPTION

TECHNICAL DATA	
Operating pressure	Min. 2 bar (g) Max. 16 bar (g)
Ambient temperature	Min. +2°C Max. +50°C
Medium temperature	Min. +2°C Max. +70°C
Medium	Compressed Air
Refrigerant	R513A
Sound pressure level (at distance of 1cm)	<70 dB (A)
Power supply	BURAN 0020 – BURAN 0105 : 220-230V / 1N / 50-60Hz BURAN 0125 – BURAN 1000 : 220-230V / 1N / 50Hz or 60Hz
Protection class	IP 23
Design, Manufacturing and Testing	Acc. to PED 2014/68/EU- Module A (Cat. I) & Module A2 (Cat. II)

SIZING

Operating pressure (bar)	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Correction factor (fp)	0.49	0.66	0.77	0.86	0.93	1.00	1.05	1.10	1.14	1.18	1.21	1.24	1.27	1.30	1.33

Compressed air inlet temperature (°C)	25	30	35	40	45	50	55	60	65	70
Correction factor (fte)	1.20	1.12	1.00	0.83	0.69	0.59	0.50	0.44	0.39	0.37

Temperature of cooling media (°C)	25	30	35	40	45	50
Correction factor (ftu)	1.00	0.96	0.90	0.82	0.72	0.60

Pressure dewpoint (°C)	3	5	7	10
Correction factor (ftpd)	1.00	1.09	1.19	1.37

Example:

$V_{nom} = 100 \text{ m}^3/\text{h}$, inlet temperature = 40°C, ambient temperature = 35°C, operating pressure = 9 bar (g), PDP = +3°C

$$V_{corr} = \frac{V_{nom}}{f} = \frac{200 \text{ m}^3/\text{h}}{0.8217} = 121.7 \text{ m}^3/\text{h}$$


Calculated dryer size:
BURAN 0125

PRODUCT SPECIFICATIONS

Type	Volume Flow (m³/h)	Volume Flow (m³/min)	Refrigerant R513A quantity (kg)	Cooling air requirement	Power consumption (total 50 / 60 Hz - kW)
DC 0020 AB	20	0.33	0.10	200	0.11 / 0.12
DC 0035 AB	35	0.58	0.12	200	0.15 / 0.17
DC 0050 AB	50	0.83	0.17	200	0.16 / 0.18
DC 0065 AB	65	1.08	0.18	200	0.17 / 0.19
DC 0085 AB	85	1.42	0.18	300	0.30 / 0.35
DC 0105 AB	105	1.75	0.23	300	0.31 / 0.36
DC 0125 AB	125	2.08	0.23	300	0.32 / 0.37
DC 0150 AB	150	2.50	0.27	300	0.33 / 0.38
DC 0180 AB	180	3.00	0.25	350	0.50
DC 0225 AB	225	3.75	0.38	380	0.56
DC 0300 AB	300	5.00	0.42	380	0.57
DC 0360 AB	360	6.00	0.55	450	0.92
DC 0450 AB	450	7.50	0.75	450	0.93
DC 0550 AB	550	9.17	0.90	450	1.50
DC 0650 AB	650	10.83	0.90	2400	1.40
DC 0750 AB	750	12.50	1.40	2400	1.50
DC 0850 AB	850	14.17	1.54	2200	1.70
DC 1000 AB	1000	16.67	1.80	2600	1.80

* acc. to ISO 7183

DIMENSIONS / WEIGHT



Type	A mm	B mm	C mm	D mm	E mm	F mm	Compressed air connections	Weight kg
0020	360	445	645	47	132	589	1/2"	27
0035	360	445	645	47	132	589	1/2"	27
0050	360	445	645	47	132	589	1/2"	28
0065	360	445	645	47	132	590	1/2"	33
0085	360	445	645	47	132	590	1/2"	33
0105	360	445	645	47	132	590	1"	35
0125	360	445	645	44	152	590	1"	36
0150	470	660	870	54	207	815	1 1/4"	50
0180	470	660	870	54	207	815	1 1/4"	52
0225	470	660	870	54	207	815	1 1/4"	54
0300	470	660	870	54	207	815	1 1/2"	58
0360	470	660	870	54	207	815	1 1/2"	63
0450	645	920	1055	79	283	968	2"	98
0550	645	920	1055	79	283	968	2"	100
0650	645	920	1055	79	283	968	2"	108
0750	645	920	1055	79	283	968	2"	127
0850	645	920	1055	79	283	968	2"	130
1000	645	920	1055	79	283	968	2"	135

For more information please contact your Donaldson Sales Representative and visit our website at www.donaldson.com.



Contact us

Donaldson Europe BV
Research Park No. 1303, Interleuvenlaan, 1
B-3001 Leuven, Belgium
Telephone: +32 (0) 16 38 38 11

Explore our solutions
at shop.donaldson.com



Technical Data Sheet No. F119325 ENG (04/25) Buran DC Refrigerated Air Dryer.

©2025 Donaldson Company, Inc. Donaldson and the color blue are marks of Donaldson Company, Inc.

All other marks belong to their respective owners. All rights reserved.

Important Notice: Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.