

STENHØJ BD REFRIGERATED DRYER

STENHØJ BD Series Refrigerated Dryer

- Aluminum heat exchanger with three functions: air-to-air exchanger, air-to-refrigerant exchanger, and condensate separator.
- Available in many versions to suit different needs
- User-friendly control system
- Dew point: 5° C

Description

Model Type BD For post-treatment of compressed air, we recommend STENHØJ's compact refrigerated dryer with a built-in water separator and high performance.

Refrigerated dryers are used to remove condensate, ensuring a low dew point in the compressed air.

Stenhøj's refrigerated dryer features an aluminum heat exchanger with three functions: air-to-air exchanger, air-to-refrigerant exchanger, and condensate separator.

Gå til produktsiden for at læse mere

Versioner

The BD series refrigerated dryer has an effective capacity of 0.33-14.17 m³/min. Available in many versions. 757427 - BD0020: 0.33 m³/min, dimensions (L*W*H) 360*645*410 mm, weight 24 kg 757428 - BD0035: 0.58 m³/min, dimensions (L*W*H) 360*645*410 mm, weight 26 kg 757429 - BD0050: 0.83 m³/min, dimensions (L*W*H) 360*645*410 mm, weight 27 kg 757430 - BD0065: 1.08 m³/min, dimensions (L*W*H)...

Gå til produktsiden for at læse mere



SPECIFICATIONS

Performance at 7 bar	0.33-14.17 m ³ /min.
Connection	230V
Power consumption at 100% load	0.16-1.36 kW
Thread in BSP	3/8"-2"
Weight	24-155 kg

<https://stenhoj.dk/en/stenhøj-bd-refrigerated-dryer-6>

HEAD OFFICE

Helge Nielsens Allé 7A
8723 Løsning

76 82 12 22

CONTACT

salgdk@stenhoj.dk
www.stenhoj.dk



<https://stenhoj.dk/en/stenhøj-bd-refrigerated-dryer-6>

HEAD OFFICE

Helge Nielsens Allé 7A
8723 Løsning

 76 82 12 22

CONTACT

 salgdk@stenhoj.dk
 www.stenhoj.dk



STENHØJ