



STENHØJ 30 BAR STARTING AIR COMPRESSOR

W-3 cylinder, air cooled, belt driven, oil lubricated, 2-stage, cast iron piston compressor, Low speed marine compressor ribbed and plate coolers. Safety valves, drain and unloading valves for LP and HP stages. Base mounted with electric motor and belt guard. Incl. of vibration dampers for floor standing or fixing to floor and stainless steel welded connecting hose. Customizable options: Precabled DOL motor starter, pre-cabled electric panel with star-delta starter, pressure switch and test certificates from DNV or BV classification societies.



TYPE	HX-2 NEO	HX-3 NEO	HX-6 NEO
Max pressure	30 bar	30 bar	30 bar
Effect	185 litre/min.	305 litre/min.	630 litre/min.
Rotation	435 rpm	720 rpm	600 rpm
Motor	4 kW	5,5 kW	11 kW
Electrical connection	220-440V/50-60Hz	220-440V/50-60Hz	220-440V/50-60Hz
Dimensions	L102xD45xH72cm	L102xD45xH73cm	L102xD45xH85cm
Installation footprint	W70xD24cm Ø14	W70xD24cm Ø14	W85xD32cm Ø14
Weight	167 kg	175 kg	250 kg
Connection	½" RG	½" RG	¾" RG

Nexion Northern Europe A/S
Barrit Langgade 188-190
DK-7150 Barrit

Phone +45 76 82 12 22
E-mail: salgdk@stenhoj.dk
Web: www.stenhoj.dk