

Wheel support devices

Standard version (400 mm) | Offroad version (500 mm)



Application

- Body work
- Repair and maintenance

Description:

The wheel support devices are exclusively designed for use on AUTOPSTENHOJ inground swivel arm lifts as well as on the surface-mounted lifts „Maestro 2.35 Premium“, „Maestro 2.35 Sport“, „Maestro 35 M/H“, and „Maestro 2.50/2.55/2.65“.

- Free access to the vehicle's underbody, ideal also for electric vehicles (battery exchange).
- Can be used independently of brand and model of vehicle.
- Wheels are not out of suspension.
- Ideal, if the working place cannot/should not be changed.
- Minimum changeover time: Wheel support devices are plugged into the swivel arms instead of the available lifting pads.
- Quick and easy lifting due to the simple positioning of the wheel support devices.
- Rim mirror is protected by plastic protectors against scratch.

Versions:

- Standard:**
Distance between arm grips: 400 mm
Wheel diameter: 500 - 580 mm
Rim size: 16 - 18 inch
- Offroad:**
Distance between arms grips: 500 mm
Wheel diameter: 580 - 660 mm
Rim size: 19 - 21 inch
- Lifting capacity: 875 kg (per wheel support)



Scan the QR-Code for detailed product information.

Further Information on www.autopstenhoj.com

AUTOPSTENHOJ GmbH

Sandkampstraße 90
D-48432 Rheine
☎ +49 5971 8602-02
✉ info@autopstenhoj.com

AUTOPSTENHOJ GmbH

Barrit Langgade 188-190
DK-7150 Barrit
☎ +45 76 82 13 30
✉ info@autopstenhoj.com



E-vehicle: Complete underbody easily accessible



Hydrogen vehicle: Free access to the underbody



Transporter safely lifted at the wheels



Extremely flat sports cars smooth and safely grabbed

Wheel support Standard



Wheel support Offroad

